

# ATEX 型-防爆尼龙电缆接头

- 产品材料:** 尼龙+改性橡胶
- 防护等级:** IP68
- 工作温度:** -40° ~ 105°, 短时可达 120°
- 阻燃等级:** UL94V-2, 可定制 V0 级阻燃
- 防爆信息:** ATEX-NB1282 Ex e IIC Gb/Ex ta IIIC IP68 Da
- 订购说明:**

- 1) 标准四件套: O 型圈, 主体, 夹紧圈, 螺帽;
- 2) 颜色请备注, 默认黑色;
- 3) 产品价格为 (人民币: 元/套, 美元: USD/set) 。



## ATEX nylon explosion-proof cable gland

- Product material:** nylon+modified rubber
- Protection grade:** IP68
- Working temperature:** - 40 °~105 °, up to 120 ° in a short time
- Flame retardant grade:** UL94V-2, customized V0 flame retardant
- Explosion proof information:** ATEX-NB1282 Ex e IIC Gb/Ex ta IIIC IP68 Da
- Ordering Instructions:**

- 1) Standard four piece set: O-ring, main body, clamping ring, nut;
- 2) Please note the color. The default color is black;
- 3) The product price is (RMB: yuan/set, USD: USD/set).



# 公制螺纹/Metric thread

蓝江产品型号	螺纹规格	电缆范围	螺纹直径	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread diameter	Thread length	Wrench Size
PN.	M	φ mm	AG mm	GL mm	nut/cap mm
ATEX-M12-06	M12×1.5	3 ~ 6.5	12	8	15
ATEX-M16-08	M16×1.5	4 ~ 8	16	8	19
ATEX-M16-10	M16×1.5	5 ~ 10	16	8	22
ATEX-M18-10	M18×1.5	5 ~ 10	18	8	22
ATEX-M20-08	M20×1.5	4 ~ 8	20	9	24
ATEX-M20-10	M20×1.5	5 ~ 10	20	9	24
ATEX-M20-12	M20×1.5	6 ~ 12	20	9	24
ATEX-M20-14	M20×1.5	8 ~ 14	20	9	27
ATEX-M22-14	M22×1.5	8 ~ 14	22	10	27
ATEX-M24-14	M24×1.5	8 ~ 14	24	10	27
ATEX-M25-18	M25×1.5	13 ~ 18	25	11	33
ATEX-M27-18	M27×2.0	13 ~ 18	27	11	33
ATEX-M30-18	M30×2.0	13 ~ 18	30	11	33
ATEX-M32-25	M32×1.5	18 ~ 25	32	11	42
ATEX-M33-25	M33×2.0	18 ~ 25	33	11	42
ATEX-M36-25	M36×2.0	18 ~ 25	36	11	42
ATEX-M40-32	M40×1.5	22 ~ 32	40	13	52
ATEX-M42-32	M42×2.0	22 ~ 32	42	13	52
ATEX-M48-32	M48×2.0	22 ~ 32	48	13	52
ATEX-M50-38	M50×1.5	32 ~ 38	50	14	60
ATEX-M60-44	M60×2.0	37 ~ 44	60	15	65
ATEX-M63-44	M63×1.5	37 ~ 44	63	15	65
ATEX-M64-44	M64×2.0	37 ~ 44	64	15	65

# PG/G/NPT 螺纹/PG/G/NPT thread

蓝江产品型号	螺纹规格	电缆范围	螺纹直径	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread diameter	Thread length	Wrench Size
PN.	PG/G/NPT	φ mm	AG mm	GL mm	nut/cap mm
ATEX-PG7-06	PG7	3~6.5	12.5	8	15
ATEX-PG9-08	PG9	4~8	15.2	8	19
ATEX-PG11-10	PG11	5~10	18.6	8	22
ATEX-PG13.5-10	PG13.5	5~10	20.4	9	24
ATEX-PG13.5-12	PG13.5	6~12	20.4	9	24
ATEX-PG16-14	PG16	8~14	22.5	9	27
ATEX-PG21-18	PG21	13~18	28.3	11	33
ATEX-PG29-25	PG29	18~25	37	11	42
ATEX-PG36-32	PG36	22~32	47	13	52
ATEX-PG42-38	PG42	32~38	54	14	60
ATEX-PG48-44	PG48	37~44	59.3	15	65
ATEX-NPT1/4-06	NPT1/4	3~6.5	13.11	8	15
ATEX-NPT3/8-10	NPT3/8	5~10	16.66	11	22
ATEX-NPT1/2-12	NPT1/2	6~12	20.99	13	24
ATEX-NPT3/4-18	NPT3/4	13~18	26.44	13	33
ATEX-NPT1-25	NPT1	18~25	33.24	16	42
ATEX-NPT1-1/4-32	NPT1-1/4	22~32	41.91	16	52
ATEX-NPT1-1/2-38	NPT1-1/2	32~38	47.8	16	60
ATEX-NPT2-44	NPT2	37~44	59.61	16	65
ATEX-G1/4-06	G1/4	3~6.5	13.11	8	15
ATEX-G3/8-10	G3/8	5~10	16.66	11	22
ATEX-G1/2-12	G1/2	6~12	20.99	13	24
ATEX-G3/4-18	G3/4	13~18	26.44	13	33
ATEX-G1-25	G1	18~25	33.24	16	42
ATEX-G1-1/4-32	G1-1/4	22~32	41.91	16	52
ATEX-G1-1/2-38	G1-1/2	32~38	47.8	16	60
ATEX-G2-44	G2	37~44	59.61	16	65

# 公制长螺纹/Metric long thread

蓝江产品型号	螺纹规格	电缆范围	螺纹直径	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread diameter	Thread length	Wrench Size
PN.	M/PG	φ mm	AG mm	GL mm	nut/cap mm
ATEX-M12L-06	M12×1.5	3 ~ 6.5	12	15	15
ATEX-M16L-08	M16×1.5	4 ~ 8	16	15	19
ATEX-M18L-10	M18×1.5	5 ~ 10	18	15	22
ATEX-M20L-10	M20×1.5	5 ~ 10	20	15	24
ATEX-M20L-12	M20×1.5	6 ~ 12	20	15	24
ATEX-M22L-14	M22×1.5	8 ~ 14	22	15	27
ATEX-M24L-14	M24×1.5	8 ~ 14	24	15	27
ATEX-M25L-18	M25×1.5	13 ~ 18	25	15	33
ATEX-M27L-18	M27×2.0	13 ~ 18	27	15	33
ATEX-M32L-25	M32×1.5	18 ~ 25	32	15	42
ATEX-M36L-25	M36×2.0	18 ~ 25	36	15	42
ATEX-M40L-32	M40×1.5	22 ~ 32	40	15	52
ATEX-PG7L-06	PG7	3 ~ 6.5	12.5	15	15
ATEX-PG9L-08	PG9	4 ~ 8	15.2	15	19
ATEX-PG11L-10	PG11	5 ~ 10	18.6	15	22
ATEX-PG13.5L-10	PG13.5	5 ~ 10	20.4	15	24
ATEX-PG13.5L-12	PG13.5	6 ~ 12	20.4	15	24
ATEX-PG16L-14	PG16	8 ~ 14	22.5	15	27
ATEX-PG21L-18	PG21	13 ~ 18	28.3	15	33
ATEX-PG29L-25	PG29	18 ~ 25	37	15	42