

## Exe 型-防爆尼龙电缆接头

- 产品材料:** 尼龙+EPDM 橡胶
- 防护等级:** IP68
- 工作温度:** -40° ~ 105°, 短时可达 120°
- 阻燃等级:** UL94V-2, 可定制 V0 级阻燃
- 防爆信息:** Exe IIC Gb/Ex tD A20 IP68
- 订购说明:**

- 1) 标准五件套: 螺母, 垫片, 主体, 夹紧圈, 螺帽;
- 2) 颜色请备注, 可选黑色, 蓝色;
- 3) 产品价格为 (人民币: 元/套, 美元: USD/set) 。



## ATEX nylon explosion-proof cable gland

- Product material:** nylon+EPDM rubber
- Protection grade:** IP68
- Working temperature:** - 40 °~105 °, up to 120 ° in a short time
- Flame retardant grade:** UL94V-2, customized V0 flame retardant
- Explosion proof information:** ATEX-NB1282 Ex e IIC Gb/Ex ta IIIC IP68 Da
- Ordering Instructions:**

- 1) Standard four piece set: O-ring, main body, clamping ring, nut;
- 2) Please note the color. The default color is black;
- 3) The product price is (RMB: yuan/set, USD: USD/set).

☆ **Special note:** the model bar marked with \* is non-standard product, which may have no stock or only a small amount of stock



# 公制螺纹/Metric thread

蓝江产品型号	螺纹规格	电缆范围	螺纹直径	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread diameter	Thread length	Wrench Size
PN.	Metric	φ mm	AG mm	GL mm	nut/cap mm
Exe-MG12B-08	M12×1.5	4~8	12	8.5	18/19
Exe-MG12B-05	M12×1.5	3~5	12	8.5	18/19
Exe-MG16B-10	M16×1.5	6~10	16	10	22/22
Exe-MG16B-07	M16×1.5	4~7	16	10	22/22
Exe-MG18B-10	M18×1.5	6~10	18	10	24/22
Exe-MG18B-07	M18×1.5	4~7	18	10	24/22
Exe-MG20B-14	M20×1.5	8~14	20	10	27/27
Exe-MG20B-12	M20×1.5	6~12	20	10	27/24
Exe-MG20B-09	M20×1.5	5~9	20	10	27/24
Exe-MG22B-14	M22×1.5	8~14	22	10	29/27
Exe-MG25B-18	M25×1.5	13~18	25	12	33/33
Exe-MG25B-13	M25×1.5	7~13	25	12	33/33
Exe-MG25B-08	M25×1.5	4~8	25	12	33/33
Exe-MG32B-25	M32×1.5	18~25	32	15	41/41
Exe-MG32B-22	M32×1.5	16~22	32	15	41/41
Exe-MG32B-18	M32×1.5	13~18	32	15	41/41
Exe-MG32B-12	M32×1.5	8~12	32	15	41/41
Exe-MG36B-25	M36×1.5	18~25	36	12	45/41
Exe-MG40B-32	M40×1.5	24~32	40	20	50/50
Exe-MG40B-25	M40×1.5	18~25	40	20	50/50
Exe-MG50B-41	M50×1.5	31~41	50	22	62/62
Exe-MG50B-28	M50×1.5	22~28	50	22	62/62
Exe-MG63B-45	M63×1.5	35~45	63	18	75/65

# PG 螺纹/PG thread

蓝江产品型号	螺纹规格	电缆范围	螺纹直径	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread diameter	Thread length	Wrench Size
PN.	Metric	φ mm	AG mm	GL mm	nut/cap mm
Exe-PG7B-08	PG7	4 ~ 8	12.5	8.5	17/19
Exe-PG7B-05	PG7	3 ~ 5	12.5	8.5	17/19
Exe-PG9B-08	PG9	4 ~ 8	15.2	8.5	22/19
Exe-PG9B-05	PG9	3 ~ 5	15.2	8.5	22/19
Exe-PG11B-10	PG11	6 ~ 10	18.6	10	22/22
Exe-PG11B-07	PG11	4 ~ 7	18.6	10	22/22
Exe-PG13.5B-12	PG13.5	6 ~ 12	20.4	10	27/24
Exe-PG13.5B-09	PG13.5	5 ~ 9	20.4	10	27/24
Exe-PG16B-14	PG16	8 ~ 14	22.5	11	30/27
Exe-PG16B-11	PG16	6 ~ 11	22.5	11	30/27
Exe-PG16B-07	PG16	4 ~ 7	22.5	11	30/27
Exe-PG21B-18	PG21	13 ~ 18	28.3	12	36/33
Exe-PG21B-13	PG21	8 ~ 13	28.3	12	36/33
Exe-PG21B-08	PG21	4 ~ 8	28.3	12	36/33
Exe-PG29B-25	PG29	18 ~ 25	37	12	46/41
Exe-PG29B-22	PG29	16 ~ 22	37	12	46/41
Exe-PG29B-18	PG29	13 ~ 18	37	12	46/41
Exe-PG29B-12	PG29	7 ~ 12	37	12	46/41
Exe-PG36B-32	PG36	24 ~ 32	47	15	57/50
Exe-PG36B-25	PG36	18 ~ 25	47	15	57/50
Exe-PG42B-41	PG42	31 ~ 41	54	15.5	64/62
Exe-PG42B-28	PG42	22 ~ 28	54	15.5	64/62
Exe-PG48B-45	PG48	35 ~ 45	59.3	15.5	70/65

# G 螺纹/G thread

蓝江产品型号	螺纹规格	电缆范围	螺纹直径	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread diameter	Thread length	Wrench Size
PN.	Metric	φ mm	AG mm	GL mm	nut/cap mm
Exe-G1/4B-08	G1/4	4 ~ 8	13.15	8.5	19/19
Exe-G1/4B-05	G1/4	3 ~ 5	13.15	8.5	19/19
Exe-G3/8B-10	G3/8	6 ~ 10	16.66	10	22/22
Exe-G3/8B-07	G3/8	4 ~ 7	16.66	10	22/22
Exe-G1/2B-12	G1/2	6 ~ 12	20.95	10	27/24
Exe-G1/2B-09	G1/2	5 ~ 9	20.95	10	27/24
Exe-G3/4B-18	G3/4	13 ~ 18	26.44	12	33/33
Exe-G3/4B-13	G3/4	7 ~ 13	26.44	12	33/33
Exe-G3/4B-08	G3/4	4 ~ 8	26.44	12	33/33
Exe-G1B-25	G1	18 ~ 25	33.2	13.5	42/41
Exe-G1B-22	G1	16 ~ 22	33.2	13.5	42/41
Exe-G1B-18	G1	13 ~ 18	33.2	13.5	42/41
Exe-G1B-12	G1	7 ~ 12	33.2	13.5	42/41
Exe-G1-1/4B-32	G1-1/4	24 ~ 32	41.9	15	51/50
Exe-G1-1/4B-25	G1-1/4	18 ~ 25	41.9	15	51/50
Exe-G1-1/2B-41	G1-1/2	31 ~ 41	47.8	16	62/62
Exe-G1-1/2B-28	G1-1/2	22 ~ 28	47.8	16	62/62
Exe-G2B-45	G2	35 ~ 45	59.6	25	75/75

# NPT 螺纹/NPT thread

蓝江产品型号	螺纹规格	电缆范围	螺纹直径	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread diameter	Thread length	Wrench Size
PN.	Metric	φ mm	AG mm	GL mm	nut/cap mm
Exe-NPT3/8B-10	NPT3/8	6 ~ 10	16.66	10	22
Exe-NPT3/8B-07	NPT3/8	4 ~ 7	16.66	10	22
Exe-NPT1/2B-12	NPT1/2	6 ~ 12	20.95	10	27
Exe-NPT1/2B-09	NPT1/2	5 ~ 9	20.95	10	27
Exe-NPT3/4B-18	NPT3/4	13 ~ 18	26.44	15	33
Exe-NPT3/4B-13	NPT3/4	7 ~ 13	26.44	15	33
Exe-NPT3/4B-08	NPT3/4	4 ~ 8	26.44	15	33
Exe-NPT1B-25	NPT1	18 ~ 25	33.5	17	41
Exe-NPT1B-22	NPT1	16 ~ 22	33.5	17	41
Exe-NPT1B-18	NPT1	13 ~ 18	33.5	17	41
Exe-NPT1B-12	NPT1	7 ~ 12	33.5	17	41
Exe-NPT1-1/4B-32	NPT1-1/4	24 ~ 32	42	17	50
Exe-NPT1-1/4B-25	NPT1-1/4	18 ~ 25	42	17	50
Exe-NPT1-1/2B-32	NPT1-1/2	24 ~ 32	48	17	52
Exe-NPT2B-45	NPT2	35 ~ 45	60	20	68

# 公制和德制长螺纹/Metric and PG long thread

蓝江产品型号	螺纹规格	电缆范围	螺纹直径	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread diameter	Thread length	Wrench Size
PN.	Metric	φ mm	AG mm	GL mm	nut/cap mm
Exe-MG12BL-08	M12×1.5	4~8	12	15	18/19
Exe-MG12BL-05	M12×1.5	3~5	12	15	18/19
Exe-MG16BL-10	M16×1.5	6~10	16	15	22/22
Exe-MG16BL-07	M16×1.5	4~7	16	15	22/22
Exe-MG16BSL-08	M16×1.5	4~8	16	15	22/19
Exe-MG16BSL-05	M16×1.5	3~5	16	15	22/19
Exe-MG18BL-10	M18×1.5	6~10	18	15	24/22
Exe-MG18BL-07	M18×1.5	4~7	18	15	24/22
Exe-MG20BL-14	M20×1.5	8~14	20	15	27/27
Exe-MG20BL-11	M20×1.5	6~11	20	15	27/27
Exe-MG20BL-07	M20×1.5	4~7	20	15	27/27
Exe-MG20BSL-12	M20×1.5	6~12	20	15	27/24
Exe-MG20BSL-09	M20×1.5	5~9	20	15	27/24
Exe-MG25BL-18	M25×1.5	13~18	25	15	33/33
Exe-MG25BL-13	M25×1.5	7~13	25	15	33/33
Exe-MG25BL-08	M25×1.5	4~8	25	15	33/33
Exe-PG7BL-08	PG7	4~8	12.5	15	17/19
Exe-PG9BL-08	PG9	4~8	15.2	15	22/19
Exe-PG11BL-10	PG11	6~10	18.6	15	22/22
Exe-PG11BL-07	PG11	4~7	18.6	15	22/22
Exe-PG13.5BL-12	PG13.5	6~12	20.4	15	27/24
Exe-PG13.5BL-09	PG13.5	5~9	20.4	15	27/24
Exe-PG16BL-14	PG16	8~14	22.5	15	30/27
Exe-PG16BL-11	PG16	6~11	22.5	15	30/27
Exe-PG21BL-18	PG21	13~18	28.3	15	36/33
Exe-PG21BL-13	PG21	8~13	28.3	15	36/33
Exe-PG21BL-08	PG21	4~8	28.3	15	36/33

防爆基本类型有：隔爆型、增安型（本款产品）、浇封型、正压型、本安型、粉尘防爆型（本款）、本安型、粉尘防爆型、油浸型

