

快插防水连接器

- 产品材料:** 尼龙+硅胶
- 防护等级:** 配密封圈可达 IP68
- 工作温度:** -20° ~ 105°, 短时可达 120 度
- 订购说明:**

- 1) 购买前, 务必确认电缆范围及芯数;
- 2) 默认黑色尼龙, 黄色密封圈;
- 3) 产品价格为 (人民币: 元/套, 美元: USD/set) 。



Quick plug waterproof connector

- Product material:** nylon+silica gel
 - Protection grade:** IP68 with sealing ring
 - Working temperature:** - 20 °~105 °, up to 120 ° in a short time
 - Ordering Instructions:**
- 1) Before purchasing, be sure to confirm the cable range and number of cores;
 - 2) Default black nylon, yellow sealing ring;
 - 3) The product price is (RMB: yuan/set, USD: USD/set).



选型表格/Model Selection Table

蓝江产品型号	螺纹规格	锁线范围	电缆芯数	电缆截面积
Product model	Thread size	Cable range	cable cores	Cable square
PN.	M Thread	mm	pcs	mm ²
LR-M16-08-2X	M16×1.5	5~8	2 芯	0.5-1.5mm ²
LR-M16-08-3X	M16×1.5	5~8	3 芯	0.5-1.5mm ²
LR-M16-10-2X	M16×1.5	6~10	2 芯	0.5-1.5mm ²
LR-M16-10-3X	M16×1.5	6~10	3 芯	0.5-1.5mm ²
LR-M20-08-2X	M20×1.5	5~8	2 芯	0.5-2.5mm ²
LR-M20-08-3X	M20×1.5	5~8	3 芯	0.5-2.5mm ²
LR-M20-12-2X	M20×1.5	9~12	2 芯	0.5-2.5mm ²
LR-M20-12-3X	M20×1.5	9~12	3 芯	0.5-2.5mm ²
LR-M25-08-2X	M25×1.5	5~8	2 芯	0.5-2.5mm ²
LR-M25-08-3X	M25×1.5	5~8	3 芯	0.5-2.5mm ²
LR-M25-08-4X	M25×1.5	5~8	4 芯	0.5-2.5mm ²
LR-M25-08-5X	M25×1.5	5~8	5 芯	0.5-2.5mm ²
LR-M25-12-2X	M25×1.5	9~12	2 芯	0.5-2.5mm ²
LR-M25-12-3X	M25×1.5	9~12	3 芯	0.5-2.5mm ²
LR-M25-12-4X	M25×1.5	9~12	4 芯	0.5-2.5mm ²
LR-M25-12-5X	M25×1.5	9~12	5 芯	0.5-2.5mm ²
LR-M25-14-2X	M25×1.5	10~14	2 芯	0.5-2.5mm ²
LR-M25-14-3X	M25×1.5	10~14	3 芯	0.5-2.5mm ²
LR-M25-14-4X	M25×1.5	10~14	4 芯	0.5-2.5mm ²
LR-M25-14-5X	M25×1.5	10~14	5 芯	0.5-2.5mm ²