

## 接管式不锈钢防水接头

- 产品材料:** 默认304, 可选316及316L, 密封件为EPDM橡胶
- 防护等级:** IP68
- 工作温度:** -40° ~ 105°, 短时120°
- 阻燃等级:** UL94V-2, 可定制V0级阻燃
- 防爆类型:** 符合Exe 增安及ExtD 粉尘防爆
- 产品性能:** 适配挠性管及镀锌管钢管连接

### •订购说明:

- 1) 默认发货不附螺母, 如需需要单独购买, 请知悉
- 2) 默认为304材质, 如需316, 请将型号后缀 "-SS" 改成" S316"
- 3) 产品价格为 (人民币: 元/套, 美元: USD/set) ;



## Nozzle type stainless steel waterproof galnd

- Product material:** default 304, optional 316 and 316L, seal is EPDM rubber
- Protection grade:** IP68
- Operating temperature:** - 40 °~105 °, short-term 120 °
- Flame retardant grade:** UL94V-2, customized V0 flame retardant
- Explosion proof type:** in accordance with Exe increased safety and ExtD dust explosion-proof
- Product performance:** suitable for flexible pipe and galvanized pipe steel pipe connection
- Ordering instructions:**

- 1) The default delivery does not include nuts. If you need to purchase separately, please know
- 2) The default is 304 material. If 316 is required, please change the model suffix "- SS" to "S316"
- 3) The product price is (RMB: yuan/set, USD: USD/set);

### 产品应用场合/Application occasion



公制螺纹尺寸表/Metric Thread Size Table

蓝江产品型号	外螺纹	内螺纹	电缆范围	螺纹长度	扳手尺寸
Product model	M-thread	F-thread	Cable range	Thread L	Wrench Size
PN.	M	F	φ mm	GL mm	nut/cap mm
M12M-M12F-08-SS	M12×1.5	M12×1.5	4~8	9	15/17
M16M-M16F-08-SS	M16×1.5	M16×1.5	4~8	9.5	20/17
M16M-M16F-10-SS	M16×1.5	M16×1.5	6~10	9.5	20/21
M20M-M20F-12-SS	M20×1.5	M20×1.5	7~12	12	24/24
M20M-G1/2F-12-SS	M20×1.5	G1/2	7~12	12	24/24
M20M-G3/4F-12-SS	M20×1.5	G3/4	7~12	12	24/31
M20M-NPT1/2F-12-SS	M20×1.5	NPT1/2	7~12	12	24/24
M20M-NPT3/4F-12-SS	M20×1.5	NPT3/4	7~12	12	24/31
M20M-M20F-14-SS	M20×1.5	M20×1.5	8~14	12	24/26
*M20M-G1/2F-14-SS	M20×1.5	G1/2	8~14	12	24/26
*M20M-G3/4F-14-SS	M20×1.5	G3/4	8~14	12	24/31
*M20M-NPT1/2F-14-SS	M20×1.5	NPT1/2	8~14	12	24/26
*M20M-NPT3/4F-14-SS	M20×1.5	NPT3/4	8~14	12	24/31
M25M-M25F-18-SS	M25×1.5	M25×1.5	13~18	12	30/31
M25M-G3/4-18-SS	M25×1.5	G3/4	13~18	12	30/31
M25M-NPT3/4F-18-SS	M25×1.5	NPT3/4	13~18	12	30/31
M32M-M32F-25-SS	M32×1.5	M32×1.5	18~25	12.5	38/40
M32M-G1F-25-SS	M32×1.5	G1	18~25	12.5	38/40
M32M-NPT1F-25-SS	M32×1.5	NPT1	18~25	12.5	38/40
M40M-M40F-31-SS	M40×1.5	M40×1.5	25~31	14	48/50
M40M-G1-1/4F-31-SS	M40×1.5	G1-1/4	25~31	14	48/50
M40M-NPT1-1/4F-31-SS	M40×1.5	NPT1-1/4	25~31	14	48/50
M50M-M50F-41-SS	M50×1.5	M50×1.5	33~41	15	58/60
M50M-G1-1/2-41-SS	M50×1.5	G1-1/2	33~41	15	58/60
M50M-NPT1-1/2-41-SS	M50×1.5	NPT1-1/2	33~41	15	58/60
M63M-M63F-44-SS	M63×1.5	M63×1.5	36~44	15	71/65
M63M-G2F-44-SS	M63×1.5	G2	36~44	15	71/65
M63M-NPT2F-44-SS	M63×1.5	NPT2	36~44	15	71/65

**G螺纹尺寸表/G thread size table**

蓝江产品型号	外螺纹	内螺纹	电缆范围	螺纹长度	扳手尺寸
Product model	M-thread	F-thread	Cable range	Thread L	Wrench Size
PN.	G	F	φ mm	GL mm	nut/cap mm
G1/2M-G1/2F-12-SS	G1/2	G1/2	7 ~ 12	12	24/24
*G1/2M-G3/4F-12-SS	G1/2	G3/4	7 ~ 12	12	24/31
*G1/2M-M20F-12-SS	G1/2	M20×1.5	7 ~ 12	12	24/24
*G1/2M-M25F-12-SS	G1/2	M25×1.5	7 ~ 12	12	24/31
*G1/2M-NPT1/2F-12-SS	G1/2	NPT1/2	7 ~ 12	12	24/24
*G1/2M-NPT3/4F-12-SS	G1/2	NPT3/4	7 ~ 12	12	24/31
G3/4M-G3/4F-18-SS	G3/4	G3/4	13 ~ 18	12	31/31
G3/4M-G1/2F-12-SS	G3/4	G1/2	7 ~ 12	12	31/24
*G3/4M-M25F-18-SS	G3/4	M25×1.5	13 ~ 18	12	31/31
*G3/4M-M20F-12-SS	G3/4	M20×1.5	7 ~ 12	12	31/24
*G3/4M-NPT3/4F-18-SS	G3/4	NPT3/4	13 ~ 18	12	30/31
*G3/4M-NPT1/2F-18-SS	G3/4	NPT1/2	7 ~ 12	12	30/24
G1M-G1F-25-SS	G1	G1	18 ~ 25	12.5	38/40
*G1M-NPT1F-25-SS	G1	NPT1	18 ~ 25	12.5	38/40
G1M-M32F-25-SS	G1	M32×1.5	18 ~ 25	12.5	38/40
G1-1/4M-G1-1/4F-31-SS	G1-1/4	G1-1/4	25 ~ 31	14	48/50
*G1-1/4-NPT1-1/4F-31-SS	G1-1/4	NPT1-1/4	25 ~ 31	14	48/50
G1-1/2M-G1-1/2-31-SS	G1-1/2	G1-1/2	25 ~ 31	15	58/50
*G1-1/2M-NPT1-1/2-31-SS	G1-1/2	NPT1-1/2	25 ~ 31	15	58/50
G2M-G2F-44-SS	G2	G2	36 ~ 44	15	71/65
*G2M-NPT2F-44-SS	G2	NPT2	36 ~ 44	15	71/65

**NPT螺纹尺寸表/NPT thread size table**

蓝江产品型号	外螺纹	内螺纹	电缆范围	螺纹长度	扳手尺寸
Product model	M-thread	F-thread	Cable range	Thread L	Wrench Size
PN.	NPT	F	φ mm	GL mm	nut/cap mm
NPT1/2M-NPT1/2F-12-SS	NPT1/2	NPT1/2	7 ~ 12	12	24/24
NPT1/2M-NPT3/4F-12-SS	NPT1/2	NPT3/4	7 ~ 12	12	24/31
NPT1/2M-M20F-12-SS	NPT1/2	M20×1.5	7 ~ 12	12	24/24
NPT1/2M-M25F-12-SS	NPT1/2	M25×1.5	7 ~ 12	12	24/31
NPT1/2M-G1/2F-12-SS	NPT1/2	G1/2	7 ~ 12	12	24/24
NPT1/2M-G3/4F-12-SS	NPT1/2	G3/4	7 ~ 12	12	24/31
NPT3/4M-NPT3/4F-18-SS	NPT3/4	NPT3/4	13 ~ 18	12	30/31
NPT3/4M-NPT1/2F-18-SS	NPT3/4	NPT1/2	7 ~ 12	12	30/24
NPT3/4M-G3/4F-18-SS	NPT3/4	G3/4	13 ~ 18	12	31/31
NPT3/4M-G1/2F-18-SS	NPT3/4	G1/2	7 ~ 12	12	30/24
NPT3/4M-M25F-18-SS	NPT3/4	M25×1.5	13 ~ 18	12	31/31
NPT3/4M-M20F-18-SS	NPT3/4	M20×1.5	7 ~ 12	12	30/24
NPT1M-NPT1F-25-SS	NPT1	NPT1	18 ~ 25	12.5	38/40
NPT1M-G1F-25-SS	NPT1	G1	18 ~ 25	12.5	38/40
NPT1M-M32F-25-SS	NPT1	M32×1.5	18 ~ 25	12.5	38/40
NPT1-1/4M-G1-1/4F-31-SS	NPT1-1/4	G1-1/4	25 ~ 31	14	48/50
NPT1-1/4-NPT1-1/4F-31-SS	NPT1-1/4	NPT1-1/4	25 ~ 31	14	48/50
NPT1-1/2M-G1-1/2F-31-SS	NPT1-1/2	G1-1/2	25 ~ 31	15	58/50
NPT1-1/2M-NPT1-1/2F-31-SS	NPT1-1/2	NPT1-1/2	25 ~ 31	15	58/50
NPT2M-G2F-44-SS	NPT2	G2	36 ~ 44	15	71/65
NPT2M-NPT2F-44-SS	NPT2	NPT2	36 ~ 44	15	71/65