

防折弯不锈钢防水接头

- **产品材料:** 默认304, 可选316及316L, 密封件为EPDM橡胶
- **防护等级:** IP68
- **工作温度:** -40° ~ 105°, 短时120°
- **阻燃等级:** UL94V-2, 可定制V0级阻燃
- **产品性能:** 保护电缆, 抗折耐扭, 耐腐蚀

• 订购说明:

- 1) 默认发货不附螺母, 如需另外订购;
- 2) 默认为304材质, 如需316, 请将型号后缀 "-SS" 改成 "S316"
- 3) 产品价格为 (人民币: 元/套, 美元: USD/set) ;



Stress relief stainless steel waterproof gland

- **Product material:** default 304, optional 316 and 316L, seal is EPDM rubber
- **Protection grade:** IP68
- **Operating temperature:** - 40 °~105 °, short-term 120 °
- **Flame retardant grade:** UL94V-2, customized V0 flame retardant
- **Product performance:** protective cable, bending resistance, torsion resistance, corrosion resistance
- **Ordering Instructions:**

- 1) The default delivery does not include nuts, if you need to order separately;
- 2) The default is 304 material. If 316 is required, please change the model suffix "- SS" to "S316"
- 3) The product price is (RMB: yuan/set, USD: USD/set);

产品应用场合/Application occasion

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread length	Wrench Size
PN.	Metric	φ mm	GL mm	nut/cap mm
MG12-P-06-SS	M12×1.5	3~6	7	14
MG16-P-08-SS	M16×1.5	4~8	7	18
MG18-P-10-SS	M18×1.5	6~10	8	20
MG20-P-14-SS	M20×1.5	8~14	8	22
MG20-P-12-SS	M20×1.5	8~12	8	24
MG22-P-14-SS	M22×1.5	8~14	8	24
MG25-P-18-SS	M25×1.5	13~18	9	27
MG27-P-18-SS	M27×1.5	13~18	9	30
MG30-P-18-SS	M30×1.5	13~18	10	32
MG32-P-25-SS	M32×1.5	18~25	10	34