

防爆不锈钢填料函

- 产品材料:** 默认 304, 可选 316 及 316L, 密封件为硅胶
- 防护等级:** IP66
- 工作温度:** -20° ~ 180°
- 产品性能:** 符合 Exd 隔爆, Exe 增安及 ExtD 粉尘防爆
- 订购说明:**

- 1) 默认五件一套: O型圈, 主体, 密封件, 金属垫, 压紧帽
- 2) 特别提示, 发货不附螺母, 如需另外购买
- 3) 产品价格为 (人民币: 元/套, 美元: USD/set)
- 4) 接受定制, 可加长螺纹, 定制锁线范围, 具体联系客服



Explosion proof stainless steel stuffing box

- Product material:** default 304, optional 316 and 316L, and the seal is silicone
 - Protection grade:** IP66
 - Operating temperature:** - 20 °~180 °
 - Product performance:** Exd explosion-proof, Exe increased safety and ExtD dust explosion-proof
 - Ordering Instructions:**
- 1) The default is a set of five pieces: O-ring, main body, seal, metal gasket, compression cap
 - 2) Special note: nuts are not attached to the shipment, if you need to purchase separately
 - 3) The product price is (RMB: yuan/set, USD: USD/set)
 - 4) Accept customization, lengthen the thread, customize the lock range, contact customer service for details

产品应用/Product application



产品尺寸表/Product size

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread length	Wrench Size
PN.	Metric	φ mm	GL mm	cap mm
Exd1-M20-14-SS	M20×1.5	8~14	15	26
Exd1-M25-16-SS	M25×1.5	8~16	15	30
Exd1-M25-20-SS	M25×1.5	10~20	15	38
Exd1-M32-20-SS	M32×1.5	10~20	18	38
Exd1-M32-25-SS	M32×1.5	10~25	18	46
Exd1-M40-25-SS	M40×1.5	10~25	18	46
Exd1-M40-32-SS	M40×1.5	14~32	18	50
Exd1-M50-32-SS	M50×1.5	14~32	18	50
Exd1-M50-41-SS	M50×1.5	17~41	18	62
Exd1-M63-41-SS	M63×1.5	17~41	18	62
Exd1-G1/2-14-SS	G1/2	8~14	15	26
Exd1-G3/4-16-SS	G3/4	8~16	15	30
Exd1-G3/4-20-SS	G3/4	10~20	15	38
Exd1-G1-20-SS	G1	10~20	18	38
Exd1-G1-25-SS	G1	10~25	18	46
Exd1-G1-1/4-25-SS	G1-1/4	10~25	18	46
Exd1-G1-1/4-32-SS	G1-1/4	14~32	18	50
Exd1-G1-1/2-32-SS	G1-1/2	14~32	18	50
Exd1-G1-1/2-41-SS	G1-1/2	17~41	18	62
Exd1-G2-41-SS	G2	17~41	18	62
Exd1-NPT1/2-14-SS	NPT1/2	8~14	15	26
Exd1-NPT3/4-16-SS	NPT3/4	8~16	15	30
Exd1-NPT3/4-20-SS	NPT3/4	10~20	15	38
Exd1-NPT1-20-SS	NPT1	10~20	18	38
Exd1-NPT1-25-SS	NPT1	10~25	18	46
Exd1-NPT1-1/4-25-SS	NPT1-1/4	10~25	18	46
Exd1-NPT1-1/4-32-SS	NPT1-1/4	14~32	18	50
Exd1-NPT1-1/2-32-SS	NPT1-1/2	14~32	18	50
Exd1-NPT1-1/2-41-SS	NPT1-1/2	17~41	18	62
Exd1-NPT2-41-SS	NPT2	17~41	18	62

锥形硅胶不锈钢填料函

- **产品材料:** 默认 304, 可选 316 及 316L, 密封件为硅胶
- **防护等级:** IP68
- **工作温度:** -20° ~ 200°
- **产品性能:** 高防护等级, 耐高温防腐蚀耐酸碱等
- **订购说明:**

- 1) 默认五件一套: O型圈, 主体, 密封件, 金属垫, 压紧帽
- 2) 特别提示, 发货不附螺母, 如需另外购买
- 3) 产品价格为 (人民币: 元/套, 美元: USD/set)



Conical silicone stainless steel stuffing box

- **Product material:** default 304, optional 316 and 316L, and the seal is silicone
 - **Protection grade:** IP68
 - **Operating temperature:** - 20 °~200 °
 - **Product performance:** High protection level, high temperature resistance, corrosion resistance, acid and alkali resistance, etc
 - **Ordering Instructions:**
- 1) The default is a set of five pieces: O-ring, main body, seal, metal gasket, compression cap
 - 2) Special note: nuts are not attached to the shipment, if you need to purchase separately
 - 3) The product price is (RMB: yuan/set, USD: USD/set)

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread length	Wrench Size
PN.	Metric	φ mm	GL mm	cap mm
Exd2-M20-14-SS	M20×1.5	8~14	15	30
Exd2-M20-12-SS	M20×1.5	7~12	15	26
Exd2-M20-08-SS	M20×1.5	4~8	15	26
Exd2-M20-06-SS	M20×1.5	3~6	15	26
Exd2-G1/2-14-SS	G1/2	8~14	15	30
Exd2-G1/2-12-SS	G1/2	7~12	15	30
Exd2-G1/2-08-SS	G1/2	4~8	15	26
Exd2-G1/2-06-SS	G1/2	3~6	15	26
Exd2-NPT1/2-14-SS	NPT1/2	8~14	15	30
Exd2-NPT1/2-12-SS	NPT1/2	7~12	15	26
Exd2-NPT1/2-08-SS	NPT1/2	4~8	15	26
Exd2-NPT1/2-06-SS	NPT1/2	3~6	15	26

TJ船用不锈钢填料函

- **产品材料:** 默认 304, 可选 316 及 316L, 密封件NBR
- **防护等级:** IP66
- **工作温度:** -40° ~ 105°
- **产品性能:** 广泛应用于船舶, 耐油及一般油脂等
- **订购说明:**

- 1) 默认六件一套: 螺母, 垫片, 主体, 密封件, 金属垫, 压紧帽
- 2) 产品价格为 (人民币: 元/套, 美元: USD/set)
- 3) 本产品接受定制螺纹, 长度及锁线范围



TJ marine stainless steel stuffing box

- **Product material:** default 304, optional 316 and 316L, seal NBR
- **Protection grade:** IP66
- **Operating temperature:** - 40 ° ~ 105 °
- **Product performance:** widely used in ships, oil resistant and general grease
- **Ordering Instructions:**

- 1) The default is a set of six pieces: nut, gasket, main body, seal, metal gasket, compression cap
- 2) The product price is (RMB: yuan/set, USD: USD/set)
- 3) This product accepts custom thread, length and lockwire range

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread length	Wrench Size
PN.	Metric	φ mm	GL mm	nut/cap mm
TJ08-M14-SS	M14×1.0	5 ~ 7	10	18/18
TJ13-M18-SS	M18×1.0	9 ~ 12	11	24/24
TJ16-M22-SS	M22×1.0	11 ~ 15	12	27/28
TJ19-M27-SS	M27×1.5	14 ~ 18	14	32/32
TJ24-M30-SS	M30×1.5	18 ~ 23	14	38/38
TJ28-M36-SS	M36×2.0	23 ~ 27	14	45/45
TJ34-M42-SS	M42×2.0	27 ~ 33	14	50/50
TJ42-M52-SS	M52×2.0	33 ~ 41	14	62/60
TJ50-M58-SS	M58×2.0	33 ~ 49	20	65/70
TJ58-M68-SS	M68×2.0	33 ~ 57	20	85/80