

不双密封不锈钢防水接头

- 产品材料:** 默认304, 可选316及316L, 密封件为EPDM橡胶
- 防护等级:** IP68
- 工作温度:** -40° ~ 105°, 短时120°
- 阻燃等级:** UL94V-2, 可定制V0级阻燃
- 产品性能:** 双层电缆锁紧密封, 抗拉力强, 防护高

•订购说明:

- 1) 默认发货不附螺母, 如需另外购买;
- 2) 默认为304材质, 如需316, 请将型号后缀 "-SS" 改成 "S316"
- 3) 产品价格为 (人民币: 元/套, 美元: USD/set) ;
- 4) 本产品接受定制, 如螺纹, 长度, 锁线范围等



Non double sealing stainless steel waterproof galnd

- Product material:** default 304, optional 316 and 316L, seal is EPDM rubber
- Protection grade:** IP68
- Operating temperature:** - 40 °~105 °, short-term 120 °
- Flame retardant grade:** UL94V-2, customized V0 flame retardant
- Product performance:** double-layer cable locking seal, strong tensile resistance, high protection
- Ordering Instructions:**

- 1) The default delivery does not include nuts, if you need to purchase separately;
- 2) The default is 304 material. If 316 is required, please change the model suffix "- SS" to "S316"
- 3) The product price is (RMB: yuan/set, USD: USD/set);
- 4) This product is customized, such as thread, length, lock range, etc

[产品结构图/product mix](#)



产品尺寸表/Product Size Table

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread length	Wrench Size
PN.	Metric	φ mm	GL mm	nut/cap mm
SMF-MG12-08-SS	M12×1.5	4~8	9	15/17
SMF-MG12-05-SS	M12×1.5	3~5.5	9	15/17
SMF-MG16-10-SS	M16×1.5	6~10	9.5	20/21
SMF-MG16-07-SS	M16×1.5	4~7	9.5	20/21
SMF-MG20-14-SS	M20×1.5	8~14	12	24/26
SMF-MG20-12-SS	M20×1.5	7~12	12	24/24
SMF-MG20-11-SS	M20×1.5	6~11	12	24/24
SMF-MG20-09-SS	M20×1.5	5~9	12	24/24
SMF-MG25-18-SS	M25×1.5	13~18	12	30/31
SMF-MG25-16-SS	M25×1.5	12~16	12	30/31
SMF-MG25-14-SS	M25×1.5	8~14	12	30/31
SMF-MG25-13-SS	M25×1.5	7~13	12	30/31
SMF-MG25-10-SS	M25×1.5	6~10	12	30/31
SMF-MG32-25-SS	M32×1.5	18~25	12.5	38/40
SMF-MG32-22-SS	M32×1.5	17~22	12.5	38/40
SMF-MG40-31-SS	M40×1.5/2.0	25~31	14	48/50
SMF-MG40-25-SS	M40×1.5/2.0	18~25	14	48/50
SMF-MG50-41-SS	M50×1.5	33~41	15	58/60
SMF-MG50-33-SS	M50×1.5	25~33	15	58/60
SMF-MG63-44-SS	M63×1.5	36~44	15	71/65

英制G牙尺寸表/G thread size

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread length	Wrench Size
PN.	G(PF)	mm	mm	nut/cap mm
SMF-G1/4-08-SS	G1/4	4~8	9	17/17
SMF-G1/4-05-SS	G1/4	3~5.5	9	17/17
SMF-G3/8-10-SS	G3/8	6~10	9.5	21/21
SMF-G3/8-07-SS	G3/8	4~7	9.5	21/21
SMF-G1/2-12-SS	G1/2	7~12	12	24/24
SMF-G1/2-11-SS	G1/2	6~11	12	24/24
SMF-G1/2-09-SS	G1/2	5~9	12	24/24
SMF-G3/4-18-SS	G3/4	13~18	12	30/31
SMF-G3/4-16-SS	G3/4	12~16	12	30/31
SMF-G3/4-14-SS	G3/4	8~14	12	30/31
SMF-G3/4-10-SS	G3/4	6~10	12	30/31
SMF-G1-25-SS	G1	18~25	15	38/40
SMF-G1-22-SS	G1	17~22	15	38/40
SMF-G1-1/4-31-SS	G1-1/4	25~31	15	48/50
SMF-G1-1/4-25-SS	G1-1/4	18~25	15	48/50
SMF-G1-1/2-41-SS	G1-1/2	33~41	15	55/60
SMF-G1-1/2-33-SS	G1-1/2	25~33	15	55/60
SMF-G1-1/2-31-SS	G1-1/2	25~31	15	55/50
SMF-G1-1/2-25-SS	G1-1/2	18~25	15	55/50
SMF-G2-44-SS	G2	36~44	15	71/65

美制NPT牙尺寸表/NPT thread size

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread length	Wrench Size
PN.	NPT	mm	mm	nut/cap mm
SMF-NPT1/4-08-SS	NPT1/4	4~8	9	17/17
SMF-NPT1/4-05-SS	NPT1/4	3~5.5	9	17/17
SMF-NPT3/8-10-SS	NPT3/8	6~10	10	21/21
SMF-NPT3/8-07-SS	NPT3/8	4~7	10	21/21
SMF-NPT1/2-14-SS	NPT1/2	8~14	13	24/26
SMF-NPT1/2-12-SS	NPT1/2	7~12	11	24/24
SMF-NPT1/2-11-SS	NPT1/2	6~11	11	24/24
SMF-NPT1/2-09-SS	NPT1/2	5~9	11	24/24
SMF-NPT3/4-18-SS	NPT3/4	13~18	13	30/31
SMF-NPT3/4-16-SS	NPT3/4	12~16	13	30/31
SMF-NPT3/4-14-SS	NPT3/4	8~14	13	30/31
SMF-NPT3/4-10-SS	NPT3/4	6~10	13	30/31
SMF-NPT1-25-SS	NPT1	18~25	15	38/40
SMF-NPT1-22-SS	NPT1	17~22	15	38/40
SMF-NPT1-1/4-31-SS	NPT1-1/4	25~31	15	48/50
SMF-NPT1-1/4-25-SS	NPT1-1/4	18~25	15	48/50
SMF-NPT1-1/2-41-SS	NPT1-1/2	33~41	15	55/60
SMF-NPT1-1/2-33-SS	NPT1-1/2	25~33	15	55/60
SMF-NPT1-1/2-31-SS	NPT1-1/2	25~31	15	55/50
SMF-NPT1-1/2-25-SS	NPT1-1/2	18~25	15	55/50
SMF-NPT2-44-SS	NPT2	36~44	15	71/65