

防爆金属填料函

- 产品材料:** 黄铜, 硅胶
- 防护等级:** IP66
- 工作温度:** 常规-20° ~ 180°, 短时可达 200°
- 产品特性:** Exd IIC Gb/Exe IIC Gb/Ex tD A20 IP66。

•订购说明:

- 1) 特殊说明, 发货不附螺母, 如需另外购买;
- 2) 产品价格为 (人民币: 元/套, 美元: USD/set)



Explosion proof metal stuffing box

- Product material:** brass, silica gel
- Protection grade:** IP66
- Working temperature:** normal - 20 °~180 °, up to 200 ° in a short time
- Product features:** Exd IIC Gb/Exe IIC Gb/Ex tD A20 IP66.

•Ordering Instructions:

- 1) Special instructions, nuts are not attached to the shipment, if necessary, purchase separately;
- 2) The product price is (RMB: yuan/set, USD: USD/set)

•产品应用/Product application



产品尺寸表/Product size

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread length	Wrench Size
PN.	Metric	φ mm	GL mm	cap mm
Exd1-M20-14	M20×1.5	8~14	15	26
Exd1-M25-16	M25×1.5	8~16	15	30
Exd1-M32-20	M32×1.5	10~20	18	38
Exd1-M40-25	M40×1.5	10~25	18	46
Exd1-M50-32	M50×1.5	14~32	18	50
Exd1-M63-41	M63×1.5	17~41	18	62
Exd1-G1/2-14	G1/2	8~14	15	26
Exd1-G3/4-16	G3/4	8~16	15	30
Exd1-G3/4-20	G3/4	10~20	15	38
Exd1-G1-20	G1	10~20	18	38
Exd1-G1-25	G1	10~25	18	46
Exd1-G1-1/4-25	G1-1/4	10~25	18	46
Exd1-G1-1/4-32	G1-1/4	14~32	18	50
Exd1-G1-1/2-32	G1-1/2	14~32	18	50
Exd1-G1-1/2-41	G1-1/2	17~41	18	62
Exd1-G2-41	G2	17~41	18	62
Exd1-NPT1/2-14	NPT1/2	8~14	15	26
Exd1-NPT3/4-16	NPT3/4	8~16	15	30
Exd1-NPT3/4-20	NPT3/4	10~20	15	38
Exd1-NPT1-20	NPT1	10~20	18	38
Exd1-NPT1-25	NPT1	10~25	18	46
Exd1-NPT1-1/4-25	NPT1-1/4	10~25	18	46
Exd1-NPT1-1/4-32	NPT1-1/4	14~32	18	50
Exd1-NPT1-1/2-32	NPT1-1/2	14~32	18	50
Exd1-NPT1-1/2-41	NPT1-1/2	17~41	18	62
Exd1-NPT2-41	NPT2	17~41	18	62

锥形金属填料函

- 产品材料：黄铜，硅胶
- 防护等级：IP68
- 工作温度：常规-20°~180°，短时可达200°
- 产品特性：耐高温，防水防尘。
- 订购说明：
 - 1) 特殊说明，发货不附螺母，如需另外购买；
 - 2) 产品价格为（人民币：元/套，美元：USD/set）



Conical metal stuffing box

- Product material: brass, silica gel
- Protection grade: IP68
- Working temperature: normal - 20 °~180 °, up to 200 ° in a short time
- Product characteristics: high temperature resistance, waterproof and dust-proof.
- Ordering Instructions:
 - 1) Special instructions, nuts are not attached to the shipment, if necessary, purchase separately;
 - 2) The product price is (RMB: yuan/set, USD: USD/set)

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Thread length	Wrench Size
PN.	Metric	φ mm	GL mm	cap mm
Exd2-M20-14	M20×1.5	8~14	15	30
Exd2-M20-12	M20×1.5	7~12	15	26
Exd2-M20-08	M20×1.5	4~8	15	26
Exd2-M20-06	M20×1.5	3~6	15	26
Exd2-G1/2-14	G1/2	8~14	15	30
Exd2-G1/2-12	G1/2	7~12	15	30
Exd2-G1/2-08	G1/2	4~8	15	26
Exd2-G1/2-06	G1/2	3~6	15	26
Exd2-NPT1/2-14	NPT1/2	8~14	15	30
Exd2-NPT1/2-12	NPT1/2	7~12	15	26
Exd2-NPT1/2-08	NPT1/2	4~8	15	26