

PA 管-双拼波纹管

- 产品材料:** 尼龙
- 阻燃等级:** UL94V-2, 可定制 V0 阻燃
- 工作温度:** -40° ~ 105°, 短时可达 120°
- 订购说明:**
 - 1) 默认黑色, 可选灰白色, 深灰色, 橙色等
 - 2) 本款产品仅支持整卷购买, 具体联系客服
 - 3) 整卷价格为 (人民币: 元/卷, 美元: USD/volume)



PA pipe - double cable conduit

- Product material:** nylon
- Flame retardant grade:** UL94V-2, customized V0 flame retardant
- Working temperature:** - 40 °~105 °, up to 120 ° in a short time
- Ordering Instructions:**
 - 1) Default black, gray white, dark gray, orange, etc
 - 2) This product only supports the purchase of the whole volume. Please contact the customer service for details
 - 3) The price of the whole volume is (RMB: yuan/volume, USD: USD/volume)

双拼波纹管尺寸表/Double corrugated pipe size

蓝江产品型号	软管规格	内径×外径	静态弯曲半径	包装数量
Product model	Conduit size	ID×OD	Stat.r	Packing
PN.	φ mm	mm	mm	M/ring
DPA-AD10.0	AD10	8.8×13.5	15	50
DPA-AD11.0	AD11	11×16.1	15	50
DPA-AD14.0	AD14	13.2×18.7	20	50
DPA-AD16.0	AD16	16×21.5	20	50
DPA-AD20.0	AD20	20×25.7	25	50
DPA-AD23.0	AD23	23.9×31.3	35	50
DPA-AD29.0	AD29	27.3×35.5	35	50
DPA-AD37.0	AD37	32.5×43.2	40	25
DPA-AD45.0	AD45	43.1×54.2	70	25
DPA-AD70.0	AD70	67.0×79.8	95	10
DPA-AD100.0	AD100	92×106	100	10