

RKF 内牙快速波纹管接头

- 产品材料：尼龙
- 防护等级：IP65
- 工作温度：-40°~105°，短时可达120°
- 阻燃等级：UL94V-2 阻燃
- 产品特性：内丝连接，安装便捷
- 订购说明：

- 1) 默认黑色，定制灰白与深灰色
- 2) 产品价格为（人民币：元/套，美元：USD/set）



RKF internal tooth quick bellows joint

- Product material: nylon
- Protection grade: IP65
- Working temperature: - 40 °~105 °, up to 120 ° in a short time
- Flame retardant grade: UL94V-2 flame retardant
- Product features: inner wire connection, convenient installation
- Ordering Instructions:

- 1) Default black, custom grey and dark grey
- 2) The product price is (RMB: yuan/set, USD: USD/set)

产品尺寸表/Product size

蓝江产品型号	螺纹规格	适配软管	螺纹长度
Product model	Thread size	Hose	Thread length
PN.	Metric	φ mm	GL mm
RKF-M10-AD10.0	M10×1.0	AD10.0	12.5
RKF-M12-AD10.0	M12×1.5	AD10.0	10
RKF-M12-AD13.0	M12×1.5	AD13.0	12.5
RKF-M16-AD13.0	M16×1.5	AD13.0	13
RKF-M16-AD15.8	M16×1.5	AD15.8	13.5
RKF-M20-AD15.8	M20×1.5	AD15.8	13.5
RKF-M20-AD18.5	M20×1.5	AD18.5	13.5
RKF-M20-AD21.2	M20×1.5	AD21.2	14.5
RKF-M22-AD18.5	M22×1.5	AD18.5	14
RKF-M22-AD21.2	M22×1.5	AD21.2	14.5
RKF-M25-AD21.2	M25×1.5	AD21.2	15
RKF-M25-AD25.0	M25×1.5	AD25.0	15
RKF-M25-AD28.5	M25×1.5	AD28.5	16
RKF-M30-AD25.0	M30×1.5	AD25.0	15
RKF-M30-AD28.5	M30×1.5	AD28.5	15
RKF-M32-AD28.5	M32×1.5	AD28.5	16
RKF-M32-AD34.5	M32×1.5	AD34.5	17
RKF-M40-AD34.5	M40×1.5	AD34.5	17
RKF-M40-AD42.5	M40×1.5	AD42.5	26
RKF-M50-AD42.5	M50×1.5	AD54.5	26
RKF-M50-AD54.5	M50×1.5	AD54.5	28
RKF-M63-AD54.5	M63×1.5	AD54.5	28

蓝江产品型号	螺纹规格	适配软管	螺纹长度
Product model	Thread size	Hose	Thread length
PN.	Metric	φ mm	GL mm
RKF-G1/4-AD10.0	G1/4	AD10.0	12.5
RKF-G3/8-AD13.0	G3/8	AD13.0	13.5
RKF-G3/8-AD15.8	G3/8	AD15.8	13.5
RKF-G1/2-AD15.8	G1/2	AD15.8	13.5
RKF-G1/2-AD18.5	G1/2	AD18.5	13.5
RKF-G1/2-AD21.2	G1/2	AD21.2	14.5
RKF-G3/4-AD21.2	G3/4	AD21.2	14.5
RKF-G3/4-AD25.0	G3/4	AD25.0	15
RKF-G3/4-AD28.5	G3/4	AD28.5	16
RKF-G1-AD28.5	G1	AD28.5	16
RKF-G1-AD34.5	G1	AD34.5	17
RKF-G1-1/4-AD34.5	G1-1/4	AD34.5	17
RKF-G1-1/4-AD42.5	G1-1/4	AD42.5	26
RKF-G1-1/2-AD42.5	G1-1/2	AD42.5	26
RKF-G1-1/2-AD54.5	G1-1/2	AD54.5	28
RKF-G2-AD54.5	G2	AD54.5	28