

RKG-金属螺纹快速波纹管接头

•产品材料：黄铜+尼龙

•防护等级：IP65

•工作温度：-40°~105°，短时可达120°

•阻燃等级：UL94V-2 阻燃

•订购说明：

1) 标配无螺母，需要请联系客服说明

2) 默认黑色，可选灰白与深灰色

3) 产品价格为（人民币：元/套，美元：USD/set）



RKG metal thread quick bellows Connector

•Product material: brass+nylon

•Protection grade: IP65

•Working temperature: - 40 °~105 °, up to 120 ° in a short time

•Flame retardant grade: UL94V-2 flame retardant

•Ordering Instructions:

1) No nut is provided as standard, please contact customer service for instructions

2) Default black, gray and dark gray can be selected

3) The product price is (RMB: yuan/set, USD: USD/set)

直型快速波纹管接头/Straight quick pipe connector

蓝江产品型号	螺纹规格	适配软管	螺纹直径	螺纹长度
Product model	Thread size	Hose	Thread diameter	Thread length
PN.	Metric	φ mm	AG mm	GL mm
RKG-M12-AD10.0	M12×1.5	AD10	12	10
RKG-M16-AD13.0	M16×1.5	AD13	16	12
RKG-M16-AD15.8	M16×1.5	AD15.8	16	12
RKG-M20-AD15.8	M20×1.5	AD15.8	20	13
RKG-M20-AD18.5	M20×1.5	AD18.5	20	13
RKG-M20-AD21.2	M20×1.5	AD21.2	20	13
RKG-M25-AD21.2	M25×1.5	AD21.2	25	13
RKG-M25-AD25.0	M25×1.5	AD25	25	13
RKG-M25-AD28.5	M25×1.5	AD28.5	25	13
RKG-M32-AD34.5	M32×1.5	AD34.5	32	14
RKG-M40-AD42.5	M40×1.5	AD42.5	40	17
RKG-M50-AD54.5	M50×1.5	AD54.5	50	17
RKG-M60-AD54.5	M60×1.5	AD54.5	63	17
RKG-G1/4-AD10.0	G1/4	AD10	13.15	10
RKG-G3/8-AD13.0	G3/8	AD13	16.66	12
RKG-G3/8-AD15.8	G3/8	AD15.8	16.66	12
RKG-G1/2-AD15.8	G1/2	AD15.8	20.95	13
RKG-G1/2-AD18.5	G1/2	AD18.5	20.95	13
RKG-G1/2-AD21.2	G1/2	AD21.2	20.95	13
RKG-G3/4-AD21.2	G3/4	AD21.2	26.44	13
RKG-G3/4-AD28.5	G3/4	AD28.5	26.44	13
RKG-G1-AD34.5	G1	AD34.5	33.2	14
RKG-G1-1/4-AD42.5	G1-1/4	AD42.5	41.9	15
RKG-G1-1/2-AD42.5	G1-1/2	AD42.5	47.8	15