

防水尼龙波纹管弯头

- 产品材料：尼龙
- 防护等级：IP68
- 工作温度：-40°~105°，短时可达120°
- 阻燃等级：UL94V-2 阻燃
- 订购说明：
 - 1) 标配螺母，无需请联系客服说明
 - 2) 默认黑色，可选灰白色
 - 3) 产品价格为（人民币：元/套，美元：USD/set）



Waterproof nylon cable conduit elbow connector

- Product material: nylon
- Protection grade: IP68
- Working temperature: - 40 °~105 °, up to 120 ° in a short time
- Flame retardant grade: UL94V-2 flame retardant
- Ordering Instructions:
 - 1) Standard nut, no need to contact customer service for instructions
 - 2) Default black, gray and dark gray can be selected
 - 3) The product price is (RMB: yuan/set, USD: USD/set)

产品尺寸表/Product size

蓝江产品型号	螺纹规格	适配软管	螺纹直径	螺纹长度
Product model	Thread size	Hose	Thread diameter	Thread length
PN.	Metric	φ mm	AG mm	GL mm
RQW-M16-AD13.0	M16×1.5	AD13	16	15
RQW-M20-AD15.8	M20×1.5	AD15.8	20	15
RQW-M20-AD18.5	M20×1.5	AD18.5	20	15
RQW-M20-AD21.2	M20×1.5	AD21.2	20	15
RQW-M25-AD21.2	M25×1.5	AD21.2	25	15
RQW-M25-AD25.0	M25×1.5	AD25	25	15
RQW-M25-AD28.5	M25×1.5	AD28.5	25	15
RQW-M32-AD34.5	M32×1.5	AD34.5	32	15
RQW-M40-AD42.5	M40×1.5	AD42.5	40	15