

拧紧尼龙波纹管接头

•产品材料：尼龙

•防护等级：IP67

•工作温度：-40°~105°，短时可达120°

•阻燃等级：UL94V-2 阻燃

•订购说明：

1) 标配螺母，无需请联系客服说明

2) 默认黑色，其他颜色定制，咨询客服

3) 产品价格为（人民币：元/套，美元：USD/set）



Locking nylon cable conduit connector

•Product material: nylon

•Protection grade: IP67

•Working temperature: - 40 °~105 °, up to 120 ° in a short time

•Flame retardant grade: UL94V-2 flame retardant

•Ordering Instructions:

1) Standard nut, no need to contact customer service for instructions

2) Default black, customized in other colors, consult customer service

3) The product price is (RMB: yuan/set, USD: USD/set)

产品尺寸表/Product size

蓝江产品型号	螺纹规格	适配软管	螺纹直径	螺纹长度
Product model	Thread size	Hose	Thread diameter	Thread length
PN.	Metric	φ mm	AG mm	GL mm
RF-M12-AD13.0	M12×1.5	AD13	12	10
RF-M16-AD13.0	M16×1.5	AD13	16	10
RF-M16-AD15.8	M16×1.5	AD15.8	16	10
RF-M18-AD13.0	M16×1.5	AD13	18	10
RF-M18-AD15.8	M16×1.5	AD15.8	18	10
RF-M20-AD15.8	M20×1.5	AD15.8	20	10
RF-M20-AD18.5	M20×1.5	AD18.5	20	10
RF-M20-AD21.2	M20×1.5	AD21.2	20	10
RF-M24-AD21.2	M24×1.5	AD21.2	24	10
RF-M25-AD21.2	M25×1.5	AD21.2	25	10
RF-M25-AD25.0	M25×1.5	AD25	25	14
RF-M25-AD28.5	M25×1.5	AD28.5	25	14
RF-M27-AD28.5	M27×2.0	AD28.5	27	14
RF-M30-AD28.5	M30×2.0	AD28.5	30	14
RF-M32-AD28.5	M32×1.5	AD28.5	32	14
RF-M32-AD34.5	M32×1.5	AD34.5	32	14
RF-M40-AD42.5	M40×1.5	AD42.5	40	14
RF-M42-AD42.5	M42×2.0	AD42.5	42	14
RF-M48-AD42.5	M48×2.0	AD42.5	48	14
RF-M50-AD54.5	M50×1.5	AD54.5	50	14
RF-M60-AD54.5	M60×2.0	AD54.5	60	15
RF-M63-AD54.5	M63×1.5	AD54.5	63	15