

RGAD 组合铜镀镍带锁紧管接头

•产品材料：尼龙+铜镀镍

•防护等级：IP65/IP68

•工作温度：-40°~105°，短时可达120°

•阻燃等级：UL94V-2 阻燃

•订购说明：

1) 默认不配螺母，如需请单独购买。

2) IP65 应对波纹管，IP68 应对电缆锁紧

3) 产品价格为（人民币：元/套，美元：USD/set）



RGAD copper nickel plated locking cable conduit connector

•Product material: nylon+copper nickel plating

•Protection grade: IP65/IP68

•Working temperature: - 40 °~105 °, up to 120 ° in a short time

•Flame retardant grade: UL94V-2 flame retardant

•Ordering instructions:

1) No nut is provided by default, please purchase separately if necessary.

2) IP65 shall be applied to corrugated pipe and IP68 shall be applied to cable locking

3) The product price is (RMB: yuan/set, USD: USD/set)

产品尺寸表/Product size

蓝江产品型号	螺纹规格	电缆范围	适配软管	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Adapter hose	Thread L	Wrench Size
PN.	Metric	φ mm	AD mm	GL mm	nut/cap mm
RGAD10-M12-06	M12×1.5	3~6	AD10	6	14/14
RGAD13-M12-08	M12×1.5	4~8	AD13	7	14/18
RGAD13-M16-08	M16×1.5	4~8	AD13	7	17/18
RGAD15.8-M16-10	M16×1.5	6~10	AD15.8	7	20/20
RGAD15.8-M18-10	M18×1.5	6~10	AD15.8	7	20/20
RGAD21.2-M20-14	M20×1.5	8~14	AD21.2	7	24/24
RGAD18.5-M20-12	M20×1.5	7~12	AD21.2	7	22/22
RGAD15.8-M20-10	M20×1.5	6~10	AD15.8	7	20/22
RGAD21.2-M22-14	M22×1.5	8~14	AD21.2	8	24/24
RGAD21.2-M24-14	M24×1.5	8~14	AD21.2	8	24/27
RGAD28.5-M25-18	M25×1.5	13~18	AD28.5	8	30/30
RGAD25.0-M25-18	M25×1.5	13~18	AD28.5	8	30/30
RGAD21.2-M25-16	M25×1.5	12~16	AD21.2	8	27/27
RGAD21.2-M25-14	M25×1.5	8~14	AD21.2	8	24/27
RGAD28.5-M27-18	M27×1.5/2.0	13~18	AD28.5	8	30/30
RGAD28.5-M30-18	M30×1.5/2.0	13~18	AD28.5	8	30/32
RGAD34.5-M32-25	M32×1.5	18~25	AD34.5	9	40/40
RGAD28.5-M32-22	M32×1.5	16~22	AD28.5	9	34/34
RGAD34.5-M36-25	M36×1.5/2.0	18~25	AD34.5	9	40/40

RGAD42.5-M40-32	M40×1.5	25 ~ 32	AD42.5	10	50/50
RGAD34.5-M40-25	M40×1.5	18 ~ 25	AD34.5	10	40/43
RGAD42.5-M50-32	M50×1.5	25 ~ 32	AD42.5	10	50/55
RGAD54.5-M50-38	M50×1.5	32 ~ 38	AD54.5	10	58/58
RGAD54.5-M63-44	M63×1.5	36 ~ 44	AD54.5	12	64/68
RGAD10-G1/4-06	G1/4	3 ~ 6.5	AD10	6	14/16
RGAD15.8-G3/8-08	G3/8	6 ~ 10	AD15.8	7	17/18
RGAD18.5-G1/2-12	G1/2	7 ~ 12	AD18.5	8	22/22
RGAD21.2-G1/2-14	G1/2	8 ~ 14	AD21.2	8	24/24
RGAD25-G3/4-18	G3/4	13 ~ 18	AD25	8	30/30
RGAD28.5-G3/4-18	G3/4	13 ~ 18	AD28.5	8	30/30
RGAD34.5-G1-22	G1	16 ~ 22	AD34.5	9	34/34
RGAD42.5-G1-1/4-28	G1-1/4	22 ~ 28	AD42.5	10	43/45
RGAD42.5-G1-1/2-32	G1-1/2	25 ~ 32	AD42.5	10	50/52
RGAD54.5-G1-1/2-38	G1-1/2	30 ~ 38	AD54.5	10	58/58
RGAD54.5-G2-44	G2	36 ~ 44	AD54.5	12	64/64
RGAD10-NPT1/4-06	NPT1/4	3 ~ 6.5	AD10	6	14/16
RGAD15.8-NPT3/8-08	NPT3/8	6 ~ 10	AD15.8	7	17/18
RGAD18.5-NPT1/2-12	NPT1/2	7 ~ 12	AD18.5	8	22/22
RGAD21.2-NPT1/2-14	NPT1/2	8 ~ 14	AD21.2	8	24/24
RGAD25-NPT3/4-18	NPT3/4	13 ~ 18	AD25	8	30/30
RGAD28.5-NPT3/4-18	NPT3/4	13 ~ 18	AD28.5	8	30/30
RGAD34.5-NPT1-22	NPT1	16 ~ 22	AD34.5	9	34/34
RGAD42.5-NPT1-1/4-28	NPT1-1/4	22 ~ 28	AD42.5	10	43/45
RGAD42.5-NPT1-1/2-32	NPT1-1/2	25 ~ 32	AD42.5	10	50/52
RGAD54.5-NPT1-1/2-38	NPT1-1/2	30 ~ 38	AD54.5	10	58/58
RGAD54.5-NPT2-44	NPT2	36 ~ 44	AD54.5	12	64/64