

RGW 型-带锁紧式不锈钢管弯头

RGW type - stainless steel flexible pipe connector



- 产品材料: 不锈钢
- 防护等级: IP68
- 工作温度: -40° ~ 105°

- Product material: stainless steel
- Protection grade: IP65
- Operating temperature: - 40 ° ~ 105 °

蓝江产品型号	螺纹规格	电缆范围	适配软管	螺纹长度
Product model	Thread size	Cable range	Adapter tube	Thread length
PN.	Metric	φ mm	φ mm	GL mm
RGW12-M20-12-SS	M20×1.5	7 ~ 12	φ12	12
RGW15-M20-14-SS	M20×1.5	8 ~ 14	φ15	12
RGW20-M25-18-SS	M25×1.5	13 ~ 18	φ20	12
RGW25-M32-25-SS	M32×1.5	18 ~ 25	φ25	12.5
RGW32-M40-32-SS	M40×1.5	25 ~ 31	φ32	14
RGW32-M40-25-SS	M40×1.5	18 ~ 25	φ32	14
RGW38-M50-41-SS	M50×1.5	33 ~ 41	φ38	15
RGW38-M50-33-SS	M50×1.5	25 ~ 33	φ38	15
RGW51-M63-54-SS	M63×1.5	46 ~ 54	φ51	15

蓝江产品型号	螺纹规格	电缆范围	适配软管	螺纹长度
Product model	Thread size	Cable range	Adapter tube	Thread length
PN.	Metric	φ mm	φ mm	GL mm
RGW15-G1/2-14-SS	G1/2	8 ~ 14	φ15	12
RGW12-G1/2-12-SS	G1/2	7 ~ 12	φ15	12
RGW12-G1/2-11-SS	G1/2	6 ~ 11	φ12	12
RGW12-G1/2-09-SS	G1/2	5 ~ 9	φ12	12
RGW20-G3/4-18-SS	G3/4	13 ~ 18	φ20	12
RGW20-G3/4-16-SS	G3/4	12 ~ 16	φ20	12
RGW25-G1-25-SS	G1	18 ~ 25	φ25	15
RGW25-G1-22-SS	G1	17 ~ 22	φ25	15
RGW32-G1-1/4-31-SS	G1-1/4	25 ~ 31	φ32	15
RGW32-G1-1/4-25-SS	G1-1/4	18 ~ 25	φ32	15
RGW38-G1-1/2-41-SS	G1-1/2	33 ~ 41	φ38	15
RGW38-G1-1/2-33-SS	G1-1/2	25 ~ 33	φ38	15
RGW32-G1-1/2-31-SS	G1-1/2	25 ~ 31	φ32	15
RGW32-G1-1/2-25-SS	G1-1/2	18 ~ 25	φ32	15
RGW51-G2-44-SS	G2	36 ~ 44	φ51	15

