

DPJ 型-端接式铜镀镍管接头

DPJ type - Brass flexible pipe connector

•产品材料：黄铜镀镍

•防护等级：IP65

•工作温度：-40°~105°

•Product material: Brass

•Protection grade: IP65

•Operating temperature: - 40 ° ~ 105 °



蓝江产品型号	适配软管	公制螺纹	螺纹长度	扳手尺寸
Product model	hose	M Thread	Thread length	Wrench Size
PN.	φ mm	M	GL mm	cap mm
DPJ-M16B-10	φ10	M16×1.5	10	24
DPJ-M20B-12	φ12	M20×1.5	10	27
DPJ-M20B-15	φ15	M20×1.5	12	30
DPJ-M20B-20	φ20	M20×1.5	12	36
DPJ-M25B-20	φ20	M25×1.5	12	36
DPJ-M32B-25	φ25	M32×1.5	15	42
DPJ-M40B-32	φ32	M40×1.5	15	52
DPJ-M50B-38	φ38	M50×1.5	16	60
DPJ-M63B-51	φ51	M63×1.5	16	75
DPJ-G3/8B-10	φ10	G3/8	10	24
DPJ-G3/8B-12	φ12	G3/8	10	26
DPJ-G1/2B-15	φ15	G1/2	12	30
DPJ-G3/4B-20	φ20	G3/4	12	36
DPJ-G1B-25	φ25	G1	15	42
DPJ-G1-1/4B-32	φ32	G1-1/4	15	52
DPJ-G1-1/2B-38	φ38	G1-1/2	15	60
DPJ-G2B-51	φ51	G2	15	75
DPJ-NPT3/8B-10	φ10	NPT3/8	10	24
DPJ-NPT3/8B-12	φ12	NPT3/8	10	26
DPJ-NPT1/2B-15	φ15	NPT1/2	12	30
DPJ-NPT3/4B-20	φ20	NPT3/4	12	36
DPJ-NPT1B-25	φ25	NPT1	15	42
DPJ-NPT1-1/4B-32	φ32	NPT1-1/4	15	52
DPJ-NPT1-1/2B-38	φ38	NPT1-1/2	15	60
DPJ-NPT2B-51	φ51	NPT2	15	75

RG 型-带锁紧铜镀镍管接头

RG type - Brass flexible pipe connector

•产品材料：黄铜镀镍

•防护等级：IP66

•工作温度：-40° ~ 105°

•Product material: Brass

•Protection grade: IP66

•Operating temperature: - 40 ° ~ 105 °



蓝江产品型号	螺纹规格	电缆范围	适配软管	螺纹长度
Product model	Thread size	Cable range	Adapter tube	Thread length
PN.	Metric	φ mm	φ mm	GL mm
RG8-M12-08-SS	M12×1.5	4 ~ 8	φ6	9
RG12-M16-10-SS	M16×1.5	6 ~ 10	φ10	9.5
RG12-M20-12-SS	M20×1.5	7 ~ 12	φ12	12
RG15-M20-14-SS	M20×1.5	8 ~ 14	φ15	12
RG20-M20-14-SS	M20×1.5	8 ~ 14	φ20	12
RG20-M25-18-SS	M25×1.5	13 ~ 18	φ20	12
RG25-M32-25-SS	M32×1.5	18 ~ 25	φ25	12.5
RG32-M40-28-SS	M40×1.5	22 ~ 28	φ32	14
RG38-M50-38-SS	M50×1.5	30 ~ 38	φ38	15
RG51-M63-44-SS	M63×1.5	36 ~ 44	φ51	15
RG15-G1/2-14-SS	G1/2	8 ~ 14	φ15	12
RG20-G3/4-18-SS	G3/4	13 ~ 18	φ20	12
RG25-G1-25-SS	G1	18 ~ 25	φ25	15
RG32-G1-1/4-28-SS	G1-1/4	22 ~ 28	φ32	15
RG38-G1-1/2-38-SS	G1-1/2	30 ~ 38	φ38	15
RG51-G2-44-SS	G2	36 ~ 44	φ51	15