

## 内迫式金属防水接头

- 产品材料:** 黄铜镀镍, 改性橡胶
- 防护等级:** IP68
- 工作温度:** 常规-40° ~ 105°, 短时可达 120°
- 阻燃等级:** UL94V-2, 可定制 V0 级阻燃
- 订购说明:**
  - 1) 默认四件套: O 型圈, 主体, 密封圈, 螺帽;
  - 2) 特殊说明, 发货不附螺母, 如需另外购买;
  - 3) 产品价格为 (人民币: 元/套, 美元: USD/set)



## Brass nickel plated waterproof cable gland

- Product Material:** Brass nickel plated, modified rubber
- Protection level:** IP68
- Working temperature:** conventional -40 °~105 °, short-term up to 120 °
- Flame retardant grade:** UL94V-2, customizable V0 grade flame retardant
- Ordering instructions:**
  - 1) Default four piece set: O-ring, body, sealing ring, nut;
  - 2) Special instructions, the shipment does not include nuts, if additional purchase is required;
  - 3) The product price is (RMB: yuan/set, USD: USD/set)

## 产品尺寸表

| 蓝江产品型号        | 螺纹规格       | 电缆范围        | 螺纹长度          | 扳手尺寸        |
|---------------|------------|-------------|---------------|-------------|
| Product model | Thread     | Cable range | Thread length | Wrench Size |
| PN.           | M/PG/G/NPT | φ mm        | GL mm         | cap mm      |
| MG6A-03       | M6×1       | 2-3         | 6             | 9           |
| MG8A-05       | M8×1       | 3-5         | 6             | 11          |